

AVIPC381B 15M IR IP DOME

	<p>Feature</p> <ul style="list-style-type: none"> ◆ Sensor Resolution: 420TVL ◆ Lens Type(Optical zoom Capability): 6.0mm fixed lens ◆ Day & Night: 20 pcs IR LEDs ◆ Video Compression: 4 video profiles simultaneously <ol style="list-style-type: none"> 1) MPEG4 VGA 2) MPEG4 QVGA 3) MPEG4 QQVGA 4) MJPEG VGA/ QVGA/ QQVGA (selectable) ◆ IR Distance: 15 M IR distance ◆ Resolution: 640*480/ 320*240/ 160*120 ◆ UPnP Level: UPnP Discover & Auto port forwarding
---	---

Specifications

Model No.	AVIPC381B
LAN	10/100MB
Video/ Audio	
Image Sensor	1/3" Sony CCD
Sensor Resolution	420TVL
Lens Type(Optical zoom Capability)	6mm fixed lens
Video Compression	4 video profiles simultaneously 1) MPEG4 VGA/ 2) MPEG4 QVGA / 3) MPEG4 QQVGA 4) MJPEG VGA/ QVGA/ QQVGA (selectable)
Resolution	640*480/ 320*240/ 160*120
Image Frame Rate	Max. 30 fps(N), 25fps (P) for all resolutions
Day & Night	20 pcs IR LEDs
IR Distance	15 M IR distance
2-way Audio	Simplex / Duplex 2-way audio
3GPP Cell phone	3GPP mobile surveillance. Audio+video
System	
OS	WindowsR 2000, XP, Vista
Browser	IE 6.0 or latter
Easy DDNS Service	DIPS®

UPnP Level	UPnP Discover & Auto port forwarding
I/O port	
DI/ DO Ports	DI: 1/DO: 1
RS-485	v
Video Output	BNC video out
Audio Input/Output	Line in /Line out
Motion Detection	4 zones
Pre-recording	v
Send E-Mail/ FTP	v
Voice Alert	v
Construction	Indoor use. 3-xis camera cradle
NVR Software	
Bundle	Free 16ch. CMS "SecuGuard"
Professional	16ch. Multi-brand software, or 64ch. Pro. Software (option)