


AVIPSP-IPPT/IR

	<p>Feature</p> <ul style="list-style-type: none"> ◆ Compact Size ◆ IE,AP and cellular phone ◆ Built in video server for LAN and WAN surveillance ◆ Easy to mount ◆ Options on CCD,lens and night vision capability ◆ Alarm I/O function for remote notification and intrusion ◆ Shipped with 4-view NVR program
---	---

Specifications

Model		AVIPSP-IPPT/IR
CCD		1/4-inch SONY
View Range	Pan	0~360°
	Tilt	0~90°
Moving Speed	Per Second	12~240° (Selectable)
Alarm I/O	Input/Output	2 Inputs / 1 Output
Control Signal	Format/Range	RJ-45
Power		DC12V
		AC24V
Camera Resolution/TV line	Height	480/380 TV Lines
Light Sensitivity	lux	0.3/0 lux with/IR
Focal Length	mm	6.0
Aperture		F2.0
Connectivity	Network	RJ-45
Power	Video Out	RCA-Jack
Dimension		126mm x 163mm (D x H)
Weight	g	454g / 474g
REC. Mode		Normal, Schedule, Motion detect, Alarm
Playback Mode		Date / Time search or event search

Functions

Model		AVIPSP-IPPT/IR
Resolution options		640x480, 320x240, 160x120
Remote Management		Internet/Intranet configuration and management
Network Function (RJ45)		Protocol: SMTP, FTP, DHCP, TFTP, ARP, TCP/IP, UDP
Event Control		Built-in motion detection
		Pre/Post alarm image snapshot
		Real-time E-mail notification
		Real-time FTP image notification
Video	Video input	Composite Video input
	Video format	NTSC or PAL (auto detection)
	Compression	JPEG / Motion JPEG
	Bandwidth	Adjustable bit-rate control
	Utilization	
Procession	Resolution	640x480 VGA, 320x240 QVGA, 352x288 CIF, 176x144 QCIF
	Performance	30fps@QVGA/CIF/QCIF, 15fps@VGA
	Image Controls	Brightness, Contrast, Hue, Saturation, Sharpness, Quality level, Mirror
4-View DVR software bundled		Video recording/playback