

AVSPD-IPAT886PTZ



Feature:

- ◆ AT886 Series · Indoor, Vandal proof
- ◆ AT888 Series · Outdoor Housing, Heater & Blower
- ◆ Video up to 30fps and D1 quality and VGA/CIF/QCIF option
- ◆ 3 Area motion detection setting separately
- ◆ Event triggered video can be sent via FTP or E-mail
- ◆ Support PDA /IE view(IP Model)
- ◆ Smart Phone remote view/AP view software (PH Model)
- ◆ Revolutionary New Auto Track (AT Model)
- ◆ With 16 CH recording software
- ◆ Dual Mode MPEG-4 or M-JPEG
- ◆ Audio Compression PCM/ADPCM Option
- ◆ Protocols TCP/IP, ICMP, HTTP, FTP, SMTP, DDNS, PPPoE
- ◆ 2 layers password protection
- ◆ Support on-line Firmware Upgrade
- ◆ Support network on-line video recording with AVI format
- ◆ Fully Microsoft Windows Media Player compatible
- ◆ Privacy Masking
- ◆ Controlling PTZ camera, DI/DO, & alarm equipment remotely
- ◆ Security: Random generation encode on
- ◆ 23x Optical Zoom, 10x Electronic Zoom
- ◆ Smart Optical Low Pass Filter (O.L.P.F) switching mechanism allows changing Between color and monochrome
- ◆ Remote control & set up through both infrared and RS-485
- ◆ On Screen Display Manual
- ◆ No key pad needed, equipped with remote controller StreamingImage & Sound Through MobilePhone(PH)
- ◆ Non- PC service, Stand-alone unit
- ◆ Advanced MPEG-4 video compression of streaming image and GSM-AMR audio compression technology, more efficient and better quality.

- ◆ Play real time video and audio on GPRS, PHS, WCDMA, CDMA, CDMA 2000UMTS, 3G mobile phones(PH), PDA and PC directly from(IP) IP Dome Camera, No video server needed in between.
- ◆ For 3GPP2 standard, satisfy the 3G and 2.5G mobile users.
- ◆ Support PPPoE
- ◆ User-friendly web UI allow user to setup & configuration remotely.
- ◆ Automatic network addressing function.
- ◆ External input switch allow user to receive external signal (Such as another camera, TV program, DVD player)
- ◆ Controlling PTZ camera, DI/DO, & alarm equipment remotely.
- ◆ Security: Random generation encode on steaming image

Specifications

Model	AVSPD-IPAT886PTZ
Pick-UP Device	1/4" COLOR SONY EXVIEW HAD CCD (Day & Night)
Sync System	Internal synchronous
Resolution	520 TVL
Effective Pixels	NTSC : 410K Pixel / PAL : 470K Pixel
Sensitivity	0.1 Lux (Color) / 0.02 Lux (B/W) / 0.002 Lux (SU)
Lens	23x Zoom lens f 3.6~82.8mm / F 1.6~3.8
Electronic Zoom	10x Digital zoom
S/N Ratio	50dB (AGC OFF)
IR-Cut Filter/ Focus	Auto / Manual
Electronic shutter	NTSC:1/60 ~ 1/100,000 Sec. / PAL:1/50 ~ 1/100,000 Sec.
Video output	1.0 Vp-p, 75Ω
α Correction	0.45 / 1
Gain Control	Super AGC 0 ~ 36dB
White Balance	ATW 2500° ~ 9500°XK Preset / Manual
BLC	Super BLC / 48 zone BLC
OSD Function	OSD Menu
Rotation mode	Auto Pan Feature / Preset Position Patrol / Auto-Flip
Rotation angle	Horizontal Pan 0° ~ 375° / Vertical Tilt 0° ~ 95°
Rotation speed	Horizontal Pan 400°/sec / Vertical Tilt 330° /sec
Speed setting	Auto: Approx. 2.5~60°/sec (Variable) / Manual: Approx.
Stop times	5 ~ 255 Sec (Variable)
Alarm inputs/ outputs	4 inputs/1output
Preset	62 Points
Auto Tracking/Privacy Masking	Yes
Control	Infrared Remote Control + RS-485 Control