


DVR

	<p>Feature:</p> <ul style="list-style-type: none"> ✧ Connectable to HDTV, AHD and analog cameras ✧ 16-ch synchronous playback ✧ 2 SATA interfaces ✧ UTP supported
-----------------------------------------------------------------------------------	--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

MODEL		DFT3216U
Video/Audio input	Video compression	H.264+/H.264
	Analog video input	16 ch
		BNC interface (1.0 Vp-p, 75 Ω), supporting coaxitron connection
	HDTV input	1080p25, 1080p30, 720p25, 720p30, 720p50, 720p60, 3 MP
	AHD input	1080p25, 1080p30, 720p25, 720p30
	CVBS input	Support
	IP video input	2-ch, Up to 4 MP resolution
	Audio compression	G.711u
Video/Audio output	Audio input	4-ch, RCA (2.0 Vp-p, 1 KΩ)
	CVBS output	1-ch, BNC (1.0 Vp-p, 75 Ω), resolution: PAL: 704 × 576, NTSC: 704 × 480
	HDMI/VGA output	VGA: 1-ch, 1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz
HDMI: 1-ch, 4K (3840 × 2160)/30Hz, 2K (2560 × 1440)/60Hz, 1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz		

	Encoding resolution	3 MP/1080p/720p/WD1/4CIF/VGA/CIF
	Frame rate	Main stream: 3MP @ 15fps;1080p/720p/WD1/4CIF/VGA/CIF @25fps (P)/30fps (N)
		Sub-stream: WD1/4CIF @12fps;CIF/QVGA/QCIF @25fps(P)/30fps (N)
	Video bit rate	32 Kbps to 10 Mbps
	Audio output	1-ch, RCA (Linear, 1 K Ω)
	Audio bit rate	64 Kbps
	Dual stream	Support
	Stream type	Video, Video & Audio
	Synchronous playback	16 ch
Network management	Remote connections	128
	Network protocols	TCP/IP, PPPoE, DHCP, Hik Cloud P2P, DNS, DDNS, NTP, SADP, NFS, iSCSI, UPnP™, HTTPS, ONVIF
Hard disk	SATA	2 SATA interfaces
	Capacity	Up to 6 TB capacity for each disk
External interface	Two-way audio input	1-ch, RCA (2.0 Vp-p, 1 K Ω) (using the audio input)
	Network interface	1, RJ45 10M/100M/1000M self-adaptive Ethernet interface
	USB interface	Frontpanel:1xUSB2.0 Rear panel:1xUSB3.0
	Serial interface	RS-485 (half-duplex)
	Alarm in/out	16/4
General	Power supply	12 VDC
	Consumption (without HDD)	\leq 25 W
	Working temperature	-10 $^{\circ}$ C to +55 $^{\circ}$ C (14 $^{\circ}$ F to 131 $^{\circ}$ F)
	Working humidity	10% to 90%
	Dimensions (W \times D \times H)	380 \times 320 \times 48 mm (15.0 \times 12.6 \times 1.9 inch)
	Weight (without HDD)	\leq 2 kg (4.4 lb)